




BEARING USA CORP.



7017 ACB/HCP4A Bearing 2D drawings and 3D CAD models

85 mm x 130 mm x 22 mm SKF 7017 ACB/HCP4A Angular contact ball bearing

Bearing No. 7017 ACB/HCP4A

Size	130x85x22 mm
Bore Diameter	130 mm
Outer Diameter	85 mm
Width	22 mm
d	85 mm
D	130 mm
B	22 mm
d ₁	101.7 mm
d ₂	99.3 mm
D ₂	116.4 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
a	36.3 mm
d _a - min.	91 mm
d _b - min.	91 mm
D _a - max.	124 mm
D _b - max.	126.8 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
d _n	103 mm
Basic dynamic load rating - C	25.1 kN
Basic static load rating - C ₀	22.4 kN
Fatigue load limit - P _u	0.915 kN
Limiting speed for grease	14000 r/min



BEARING USA CORP.

Lubrication	
Limiting speed for oil lubrication	22000 mm/min
Ball - D_w	9.525 mm
Ball - z	28
G_{ref}	11.02 cm ³
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	150 N
Preload class B - G_B	300 N
Preload class C - G_C	900 N
Calculation factor - f	1.08
Calculation factor - f_1	0.99
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2C}	1.05
Calculation factor - f_{HC}	1.01
Preload class A	163 N/micron
Preload class B	211 N/micron
Preload class C	316 N/micron
d_1	101.7 mm
d_2	99.3 mm
D_2	116.4 mm
$r_{1,2}$ min.	1.1 mm



BEARING USA CORP.

$r_{3,4}$ min.	0.6 mm
d_a min.	91 mm
d_b min.	91 mm
D_a max.	124 mm
D_b max.	126.8 mm
r_a max.	1 mm
r_b max.	0.6 mm
d_n	103 mm
Basic dynamic load rating C	30.2 kN
Basic static load rating C_0	33.5 kN
Fatigue load limit P_u	0.915 kN
Attainable speed for grease lubrication	14000 r/min
Attainable speed for oil-air lubrication	22000 r/min
Ball diameter D_w	9.525 mm
Number of balls z	28
Reference grease quantity G_{ref}	11.02 cm ³
Preload class A G_A	150 N
Static axial stiffness, preload class A	163 N/ μ m
Preload class B G_B	300 N
Static axial stiffness, preload class B	211 N/ μ m
Preload class C G_C	900 N
Static axial stiffness, preload class C	316 N/ μ m
Calculation factor f	1.08
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{HC}	1.01



BEARING USA CORP.

Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.9 kg